



MATERIAL SAFETY DATA SHEET

Vermitex Acustico

Not Classified as Hazardous according to criteria of Worksafe Australia

COMPANY DETAILS

Company Name L&A Fazzini Manufacturing Pty Ltd
 Address 23-25 Wentworth St Greenacre NSW 2190
 Emergency Telephone (02) 96424745
 Tel/Fax Ph: (02) 96424745 Fax: (02) 97425164

IDENTIFICATION

Product Name VERMITEX ACUSTICO
 Other Names Not Available
 Product Use Sound absorbing coating used in building construction. Material is mixed and used in accordance with manufacturers' directions. Application is by pressure spraying, or hand trowelling and rendering of walls, ceilings, beams and columns.

Physical Data

Appearance Off-white powder with off white granules. No odour. Sets and hardens when mixed with water. Slightly soluble in water and acids. Free of asbestos and other fibrogenic material.

Melting Point	Not available	Boiling Point	Not applicable
Vapor Pressure	Negligible	Specific Gravity	Not available
Flash Point	Non Flammable	Explosion Data	Not applicable

Other Properties

Form Solid

Ingredients

Ingredients	Name	CAS	Proportion
	Vermiculite (exfoliated, asbestos and silica free)	1318-00-9	30.00-80.00%
	Plaster as Calcium sulfate hemihydrate	10034-76-1	10.00-60.00%
	Foaming agent		0-10.00%

HEALTH HAZARD INFORMATION

Health Effects

Acute - Ingestion Considered an unlikely route of entry in commercial/industrial environments. The dust is irritating and may be harmful if swallowed. Ingestion may result in nausea, abdominal irritation, pain and vomiting.

Acute - Eye Generated dust is highly irritating and may be abrasive to the eyes and is capable of causing temporary discomfort with redness of the conjunctiva (similar to wind burn).

Acute - Skin The material may be irritating and slightly abrasive to the skin and may cause drying of the skin, which may lead to dermatitis.

Acute - Inhalation Generated dust is irritating to the upper respiratory tract if inhaled and may be harmful from repeated exposures over long periods. Long term exposure to high dust concentrations may cause changes in lung function, i.e. pneumoconiosis; caused by particles less than 0.5 micron penetrating and remaining in the lung. Prime symptom is breathlessness; lung shadows show on x-ray.

Chronic Principal routes of exposure are usually by skin contact with the dry or wet material and inhalation of generated dust. As with any chemical product, contact with unprotected bare skin; inhalation of vapour, mist or dust in work place atmosphere; or ingestion in any form, should be avoided by observing good occupational work practice.

First Aid

Ingestion Rinse mouth out with plenty of water. DO NOT induce vomiting. Observe the patient carefully. Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious. Provide liquid slowly and as much as casualty can comfortably drink. Seek medical advice.

Eye If this product comes in contact with the eyes: Immediately hold the eyes open and wash with fresh running water. Ensure irrigation under the eyelids by occasionally lifting upper and lower lids. If pain persists or recurs seek medical attention. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

Skin If product comes in contact with the skin: Wash affected areas thoroughly with water (and soap if available). Seek medical attention in event of irritation.

Inhalation If dust is inhaled, remove to fresh air. Encourage patient to blow nose to ensure clear breathing passages. Rinse mouth with water. Consider drinking water to remove dust from throat. If irritation or discomfort persists, seek immediate medical attention.

Advice to Doctor Treat symptomatically.

PRECAUTIONS FOR USE

Exposure Limits	Name	STEL		TWA		TWA Footnote
		mg/m3	ppm	mg/m3	ppm	
	Vermiculite (exfoliated, asbestos and silica free)			2.5		



MATERIAL SAFETY DATA SHEET

Page: 2

Vermitex Acustico

Not Classified as Hazardous according to criteria of Worksafe Australia

Other Exposure Info. None assigned for mixture. Refer to individual constituents. < vermiculite > vermiculite, containing no asbestos, as mica: TLV TWA: 3 mg/m³ respirable dust. The concentration of respirable dust for application of this limit is to be determined from the fraction that penetrates a separator whose size collection efficiency is described by a cumulative lognormal function with a median aerodynamic volume of 4.0 µm (+-) 0.3 µm and with a geometric standard deviation of 1.5 µm (+-) 0.1 µm, i.e., less than 5 µm. ES TWA: 2.5 mg/m³ inspirable dust (under review) < calcium sulfate hemihydrate > containing no asbestos and <1% crystalline silica: TLV TWA: 10 mg/m³ total dust ES TWA: 10 mg/m³ inspirable dust.

Engineering Controls Use in a well-ventilated area. General exhaust is adequate under normal operating conditions. If risk of over exposure exists, wear SAA approved dust respirator. Correct fit is essential to obtain adequate protection.

Personal Protection

Protective Equipment EYE: Safety glasses with side shields. Contact lenses pose a special hazard. Soft lenses may absorb irritants and all contact lenses concentrate them HANDS/FEET: wear physical protective gloves, e.g., leather. Wear safety footwear. OTHERS: Overalls, barrier cream. Ensure that there is ready access to eye wash unit. The local concentration of material, quantity and conditions of use determine the type of personal protective equipment required. For further information consult your Occupational Health & Safety Advisor.

Flammability

Fire Hazards Non Combustible material. Not considered to be a significant fire risk, however in a fire containers may decompose on heating and produce toxic/ corrosive fumes of sulfuroxides (SO_x) and Calcium oxide.

SAFE HANDLING INFORMATION

Storage and Transport

Storage Precautions SUITABLE CONTAINER Multi ply paper bag with sealed plastic liner or heavy gauge plastic bag. Check that all containers are clearly labelled and free from leaks. Packing as recommended by manufacturer. STORAGE INCOMPATIBILITY None known. STORAGE REQUIREMENT Keep dry. Store in original containers. Keep containers securely sealed. Store in a cool, dry, well-ventilated area. Store away from incompatible materials and foodstuff containers. Protect containers against physical damage and check regularly for leaks. Observe manufacturer's storing and handling recommendations. TRANSPORTATION No restrictions.

Spills and Disposal

Spills and Leaks MINOR SPILLS Clean up all spills immediately. Avoid contact with skin and eyes. Wear impervious gloves and safety glasses. Use dry clean up procedures and avoid generating dust. Vacuum up or sweep up. Place spilled material in clean, dry, sealable, labelled container. MAJOR SPILLS Clear area of personnel and move upwind. Alert Fire Brigade and tell them location and nature of hazard. Control personal contact by using protective equipment and dust respirator. Prevent spillage from entering drains or water courses. Recover product wherever possible. Avoid generating dust. If required, wet with water to prevent dusting. Sweep/shovel up. Put residues in labelled plastic bags or other containers for disposal. Wash area down with large quantities of water and prevent runoff into drains. If contamination of drains or waterways occurs, advise emergency services. DISPOSAL Recycle wherever possible. Consult manufacturer for recycling options. Consult State Land Waste Management Authority for disposal. Bury residue in an authorised landfill.

Fire/Explosion Hazard

Fire/Explos. Hazards Non Combustible material. Not considered to be a significant fire risk, however in a fire containers may decompose on heating and produce toxic/ corrosive fumes of sulfuroxides (SO_x) and Calcium oxide.

OTHER INFORMATION

Packaging & Labelling: Packaging as recommended by manufacturer. Paper bag with sealed plastic liner. Check that containers are clearly labelled.

CONTACT POINT

Contact In the case of an emergency, contact the Technical Manager on (02) 96424745 or, for additional information on this or other products, contact by fax on (02) 97425164. This material safety data sheet and the information contained herein, is provided for the sole purpose of enabling persons handling and using the product to do so with safety. The information herein is believed to be an accurate transcription from data sheets provided by the manufacturer.

...End of Report...